

GRAYLING INDUSTRIES, INC.  
MATERIAL SAFETY DATA SHEET

CONTROL WETTING AGENT

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: CONTROL WETTING AGENT  
Product Number: 06015  
HFR Rating: 1-1-0

MANUFACTURER: EMERGENCY PHONE NUMBER:  
Grayling Industries, Inc. (800) 535-5053 (Infotrac)  
1008 Branch Drive  
Alpharetta, GA 30004 INFORMATION: (800) 635-1551  
Date Prepared: January 5, 2001  
Date Superseded: January 31, 1995

II. COMPOSITION/INFORMATION ON INGREDIENTS

This formula contains no SARA title III regulated ingredients.  
Hazardous ingredients: None in reportable concentrations per OSHA 29 CFR  
1910.1200

III. HAZARDS IDENTIFICATION

Eye: Moderate irritant to the eyes upon repeated exposure.  
Skin: Can cause mild skin irritation upon repeated exposure.  
Swallowing: Swallowing small amounts of this material during normal  
handling is not likely to cause harmful effects. Swallowing large amounts  
may be harmful.  
Inhalation: Breathing of vapor or mist is possible. Breathing small amounts  
of this material during normal handling is not likely to cause harmful  
effects. Breathing large amounts may be harmful.  
Symptoms of Exposure: Pre-existing respiratory, skin or eye disorders may  
be aggravated by exposure.  
Cancer Information: None known.  
Other Health Effects: No data.

IV. FIRST AID MEASURES

Eyes: If irritation develops, flush eyes gently with water for at least 15  
minutes while holding eyelids open. If irritation persists, seek medical  
attention.  
Skin: Flush with water. If symptoms persist, seek immediate medical  
attention.  
Swallowing: Give victim water to induce vomiting; seek medical attention.  
Inhalation: If symptoms develop, immediately move individual away from  
exposure and into fresh air to avoid breathing mists. If symptoms persist,  
seek medical attention.

V. FIRE FIGHTING MEASURES

Flash Point: Non-Flammable Flammable Limits: N/A Fire and Explosion  
Hazards: None known  
Extinguishing Media: Water fog Fire Fighting Instructions: Not applicable

VI. ACCIDENTAL RELEASE MEASURES

Small Spills: Flush with water.  
Large Spills: Recover solution, filter, and reuse if possible. Use

absorbent material or mop to pick up spill.

#### VII. HANDLING AND STORAGE

Handling: Avoid contact with eyes; wear chemical safety goggles when handling.

#### VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Wear chemical safety goggles in compliance with OSHA regulations.

Skin Protection: Wear chemical resistant gloves (consult your safety equipment supplier).

Ventilation: Ventilate areas when spraying.

Respiratory Protection: Use NIOHS/MSHA approved respirator when spraying CONTROL Wetting Agent.

Work/Hygienic Practices: Wash with soap and water before eating, drinking, or smoking.

#### IX. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: Water - >212.0 F

Vapor Pressure: Water 24 mmHg @ 78.0 F

Specific Vapor Density: Water vapor Ca 2 @ AIR = 1

Specific Gravity: (H<sub>2</sub>O=1) 1.05

Evaporation Rate: (Butyl Acetate=1): 2

State: Liquid (like water)

Odor: Mild

Solubility in Water: Infinitely soluble

Melting Point: 32.0 F

#### X. STABILITY AND REACTIVITY

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: None known

Chemical Stability: Stable

Incompatibility: None known

#### XI. TOXICOLOGICAL & ECOLOGICAL INFORMATION

No data

#### XII. DISPOSAL CONSIDERATION

Waste Management Information: Place in suitable container for disposal of water based coatings in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs including disposal, recycling and waste stream reduction, contact Grayling Industries, Inc. at 800-635-1551.

#### XIII. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.